Gas Control Equipment

Tech Master GPD4040 Series

4.5 Purity Two Stage Brass Barstock Diaphragm Differential Autochange Gas Control Panel (BS EN ISO 7291)



The Tech Master GPD4040 Series two stage differential autochange control panels are designed for primary pressure gas control of non-corrosive or toxic, technical gases up to grade 4.5 purity (99.995%), on gas distribution systems where constant delivery pressure is required.

- **GPD4041** Series | Two Stage Twin Cylinder Diaphragm Differential Autochange Gas Control Panel, FKM Seal, FKM Pressure Relief Valve
- **GPD4042** Series | Two Stage Twin Cylinder Diaphragm Differential Autochange Gas Control Panel, EPDM Seal, EPDM Pressure Relief Valve

FEATURES

- High pressure isolation valves
- Two stage pressure regulation
- Process line isolation valve
- Encapsulated valve design
- Twin cylinder configuration

MATERIAL


Body	Brass Barstock
Valve Seat	Polyamide (Nylon®)
Seal Option	FKM / EPDM
Filter	10 Micron 316L Stainless Steel
Outlet Regulators	
Bonnet	High Strength Alloy
Diaphragm	Polychloroprene (Neoprene®) (CR)
Pre-Set & Duty-Bank Regulators	
Bonnet	Brass
Bonnet Seal	PTFE
Diaphragm	316L Stainless Steel

SPECIFICATION

Maximum Inlet Pressure	15 bar (220 PSI) 60 bar (870 PSI) 300 bar (4350 PSI) *
Delivery Pressure Range	3.5 bar (50PSI) 6.0 bar (90PSI) 10 bar (150 PSI)
Gauges	50mm (2") Diameter
Ports	1/4" NPT Female
Temperature Range	-20° C to +60° C (-4° F to +140° F)
Weight	8.0 kg (17.46 lbs) ****


** Subject to cylinder connection – **** Subject to final configuration*


FLOW PERFORMANCE




We do everything we can to ensure that the technical information within this document is correct at time of publishing, however content may be changed without notice.

DRAWINGS







MODEL NO. SELECTOR GUIDE

Example for a Model No. for GPD4040 Series

GPD4041- 02- 03- 00- 00- 000- 00- A

Product Type	Inlet Pressure Bar [PSI]	Outlet Pressure Bar [PSI]	Inlet Pressure Gauge	Outlet Pressure Gauge	Inlet/Cylinder Connection	Outlet Connection	Options
GPD4041	**02** 60 [870]	**03** 0 to 3.5 [50]	**00** No Gauge Fitted	**00** No Gauge Fitted	**000** 1/4 NPT Female	**00** 1/4 NPT Female	**A** No Options Selected
GPD4042	**04** 300 [4350]	**04** 0 to 6 [90]	**01** bar/PSI	**01** bar/PSI	**001** 1/8 Stainless Steel Compression	**01** 1/8 Stainless Steel Compression	**K** Certificate of Conformity
	06 15 [220]	**05** 0 to 10 [150]	**02** bar/PSI Contact Gauge		**002** 1/4 Stainless Steel Compression	**02** 1/4 Stainless Steel Compression	**M** CO2 Burst Disc
					003 6mm Stainless Steel Compression	**03** 6mm Stainless Steel Compression	**P** Calibration/ Pressure Test Certificate
					004 1/4 NPT Male	**04** 1/4 NPT Male	**R** Fitted Pipeline Pressure Relief Valve
					007 G3/8 BSP R/H Brass Male	**06** G1/2 BSP R/H, Brass, Male	**T** Fitted High Pressure Purge Facility, FKM Seal
					008 G3/8 BSP L/H Brass Male	**07** G3/8 BSP R/H, Brass, Male	**U** Fitted High Pressure Purge Facility, EPDM Seal
						08 G3/8 BSP L/H, Brass, Male	**X** Special Instruction

Gas Control Equipment

CK Isotopes Ltd, Office 1&2, The Stables,
Newtown Grange Farm Buisness Park,
Desford Road, Newtown Unthank,
Leicestershire, LE9 9FL

WWW.GASCONTROLEQUIPMENT.CO.UK - Tel: 01455 360180 - Email: SALES@CK-GCE.CO.UK

GASARC BY GCE SPECIALITY

Headoffice / Factory UK
Gas-Arc Group Limited
Vinces Road | Diss | Norfolk | IP22 4WW | UK