Tech Master – GPF400

Elastomer Polymer Lined High Pressure Flexible Hose with Ceramic Non-Return Valve



FEATURES

- Ceramic Non-Return Valve (NRV)
- 1/4" NPT Female Inlet
- 1/4" NPT Male Outlet from NRV
- Anti-Whip

MATERIAL

Hose	Braided with black protective cover EN ISO14113
Fittings	Brass
Internal Lining	Polymer Elastomer Lined

The Tech Master GPF400 high pressure flexible hoses are designed for use with noncorrosive or toxic, technical gases up to grade 4.5 purity (99.995%). They are intended for use in conjunction with our gas control panels.

- **GPF400** | Elastomer Polymer Lined High Pressure Flexible Hose with Ceramic Non-Return Valve

SPECIFICATION

Maximum Working Pressure	300 bar (4350 PSI)
Temperature Range	-20° C to +60° C (-4° F to +140° F)
Weight	1.0 kg (2.20 lb) 900 mm typical

MODEL NO. SELECTOR GUIDE

Example for a Model No. for GPF400 Series

GPF400-	04-	02-	01-	00-	000-	04-	A
Product Type	**Inlet Pressure Bar [PSI]**	**Length**	**Non Return Valve**	**Colour**	**Inlet/ Cylinder Connection**	**Outlet**	**Options**
GPF400	**04** 300 [4350]	**02** 900 mm	**01** NRV fitted	**00** No options	**000** 1/4 NPT Female	**04** 1/4 NPT Male	**A** No Options Selected
		03 1800 mm			**010** BS341 No.3		**K** Certificate of Conformity
		04 3600 mm			**012** BS341 No.4		**P** Calibration / Pressure Test Certificate
					other connections available, please refer to the data sheet "Cylinder connection"		

Gas Control Equipment

CK Isotopes Ltd, Office 1&2, The Stables,
Newtown Grange Farm Buisness Park,
Desford Road, Newtown Unthank,
Leicestershire, LE9 9FL

WWW.GASCONTROLEQUIPMENT.CO.UK - Tel: 01455 360180 - Email: SALES@CK-GCE.CO.UK

GASARC BY GCE SPECIALITY

Headoffice / Factory UK
Gas-Arc Group Limited
Vinces Road | Diss | Norfolk | IP22 4WW | UK

We do everything we can to ensure that the technical information within this document is correct at time of publishing, however content may be changed without notice.