LPLAVSF | LPLAESF – DRUVA®PUR LINE REGULATOR

LINE REGULATOR | PURE LINE (BRASS CHROME PLATED) | 20m³ SERIES | ABSOLUT PRESSURE RANGE SINGLE STAGE | 4-PORT VERSION

PURITY 6.0 99.9999%

This single-stage line pressure regulator is used in gas supply systems for pure, inert, flammable, oxidising gases and gas mixtures up to gas purity 6.0. It is not usable for corrosive and / or toxic gases and their mixtures.



SPECIAL FEATURES:

- Hastelloy diaphragm tighting system to atmosphere
- Compact design
- Excellent pressure adjustment
- Designed and approved regarding ISO 7291
- Relief valve in delivery pressure side available
- Electrostatic chargeability test
  - Fulfills requirements according to ISO 80079-36; IEC TS 60079-32-1 and German TRGS 727
  - Usable in EX- areas zones 1 and 2 for gases with explosion risk group I; IIA; IIB; IIC


TECHNICAL DATA	
Working temperature:	-20 °C to +60 °C
Inlet / outlet ports:	See technical drawing
Leakage rate seat:	<5x10^{-6} mbar l/s (Helium)
Leakage rate outside:	<1x10^{-9} mbar l/s (Helium)
Filter:	1x for inlet 1x for each outlet
Weight:	1,28 kg
Flow nominal:	3 m³/h (N_2)
Material gas wettet parts:	
Regulator body:	Brass chrome plated
Regulator diaphragm:	Hastelloy
Regulator seat: LPLAVSF-Version LPLAESF-Version	 FKM EPDM
Relief valve seat: LPLAVSF-Version LPLAESF-Version	 FKM EPDM
Regulator poppet:	Brass
Pressure rates line regulator:	
Max. inlet pressure	12 bar
Delivery pressure	2 bar abs/ 3 bar abs
Pressure gauges rates (pressure rates):	-1 bar till 1,5 bar (2 bar abs)/ -1 till 5 bar (3 bar abs)
Contact gauges available – please contact us	
Cracking pressure relief valves:	1,5 bar (2 bar abs)/ 3,1 bar (3 bar abs)
Test in production:	Pressure test with Helium of each item
	Seat leakage test with Helium of each item
	Helium leak test of each regulator against atmosphere
	Test of functionality of each item
Approvals during development:	Type test in accordance with ISO 7291
	Additional life cycle test
	Electrostatic chargeability test • Fulfill requirements according ISO 80079-36; IEC TS 60079-32-1 and German TRGS 727 • Usable in EX-areas zones 1 and 2 for gases with explosion risk group I; IIA; IIB; IIC

GCE Gas Control Equipment


CK Isotopes Ltd, Office 1&2, The Stables, Newtown Grange Farm Buisness Park, Desford Road, Newtown Unthank, Leicestershire, LE9 9FL

WWW.GASCONTROLEQUIPMENT.CO.UK - Tel: 01455 360180 - Email: SALES@CK-GCE.CO.UK


TECHNICAL DRAWING:



FLOW CURVES:



DYNAMIC EXPANSION CURVES:



ORDER CODE:

Example Line Regulator | PUR Linie | Brass Chrome Plated | Low Flow | Absolute Pressure | Single Stage | 4-Port Version

LPLAVSF LPLAESF	R	D1	AX	00	BT	N14F (1/4" NPT female)	N14F (1/4" NPT female)	00	0001
	Porting	**Inlet pressure**	**Outlet pressure**	**Inlet gauge**	**Outlet gauge**	**Inlet connection**	**Oulet connection**	**Safety device**	**Relief valve connection**
	R Inlet right	D1 12 bar	AX 2 bar (abs.)	00 Without 1/4" NPT female	00 Without 1/4" NPT female	possible connections see technical drawing	possible connections see technical drawing	00 Without 1/4" NPT female	0001 – if no safety device is choosen possible connection if safety device RV is choosen see technical drawing
	L Inlet left		BX 3 bar (abs.)		01 Without (plugged)			01 Without (plugged)	
					BT Bourdon Tube gauge			RV Relief valve	

Order code (as described above) without special characters or spaces! Complete Order Code LPLAVSFRD1AX00BTN14FN14F000001

CK Isotopes Ltd, Office 1&2, The Stables, Newtown Grange Farm Buisness Park,
Desford Road, Newtown Unthank, Leicestershire, LE9 9FL

WWW.GASCONTROLEQUIPMENT.CO.UK - Tel: 01455 360180 - Email: SALES@CK-GCE.CO.UK

Link to online product configurator