

TUBE FLOWMETER

MEDIMETER®

Medimeter® is a tube flowmeter intended for accurate flow adjustment, flow indication and delivery of medical gases directly to a patient under varying conditions of temperature and inlet pressure.



ADVANTAGES

- Flat surface float allows easy and safe reading of flow values by the users
- Ergonomic design, easy for cleaning
- Available with probe connector, NIST, rail mounting with a hose and twin versions
- Soft closing mechanism
- Resistant float against impact
- **Flows - 5, 15, 30, 60 lpm**



Medimeter® with 5 lpm scale *Medimeter® with 15 lpm scale* *Medimeter® with 30 lpm scale*

MEDIMETER®




Standard version with probe



DUO version with probe



Rail clamp 50 mm NIST



Rail clamp duo 50 mm NIST



Rail clamp 25 mm NIST



Rail clamp duo 25 mm NIST



Extended probe version

TECHNICAL DATA

Gas pressure:	O_2; Air
Inlet pressure:	4,5 bar
Flow ranges:	0–5 lpm
	0–15 lpm
	0–30 lpm
	0–60 lpm
Inlet connection:	According to national standard
Outlet connection:	9/16” UNF; M12×1.25; G3/8; G 1/4 (with hose nipple)
Body material:	Nickel-plated brass
O-rings:	EPDM
Control knob:	Polyamide
Body dimensions:	
Width:	32 mm
Height:	160 mm
Depth:	60 mm
Weight:	280 g (without connector)
Temperature range:	
Storage:	- 30 °C to + 60 °C
Operation:	- 20 °C to + 60 °C
Rail clamp 25 mm	Suitable for rails 25x10, 25x8 and 30x10mm
Rail clamp 50 mm	Suitable for 50x10mm rails
Regulatory status:	Compliance with (EU) 2017/745 Medical Device Regulation
	Complies with EN 15 002 (Flow - metering devices for connection to terminal units)

ACCESSORIES



Humidifier



GCE Group
www.gcegroup.com

Art. Nr. 735100000525. Edition 2/2024. Alterations are subject to change without notice. 221024kk © 2024
All photographs are illustrative only

Gas Control Equipment